

TCM torbo LOC080 und torbo LOC120

The simple torbo for everyone

So simply to handle, that it is the ideal wet abrasive system for the rental bussiness.

The use-area of the **torboLOC** stretches over gentle cleaning of monuments and facades until to concrete - and steel-redevelopment.

- torbo

For gentle cleaning, the **torboLOC** is equipped with a fine adjustable compressed air regulating vale. In addition, there is a metering dosing valve for the abrasive mixture and the supplemental water supply, which is independent of the compressed air supply.

For renovation of steel and concrete, the **torboLOC** is equipped with an additional 11/2 inch compressed air inlet.

The compact dimensions, in addition to a set of wheels and special forklift tubes, ensure easy maneuvering and loading.

With the **torbo**-System, you reduce your overheads and save the environment!

Volume of vessel - torbo LOC080 - torboLOC120	I or dm³ (Cu. ft.)	80 (2,83) 120 (4,24)
Air connection	mm (Zoll)	19 a./or 25 (3/4 a./or 1)
Compressor-connection (min - max.)	m³/min (Cu. ft. per min) bar (PSI)	2,0 - 10,0 (70 - 350) 4,0 - 10,0 (57 - 142)
Pressurized water connection	bar (PSI)	up to 12 (up to 170)
Stream-connection	V (W)	12 (1,2)
Connection blasting hose	mm (Zoll)	38 (1 1/2)
Consumption of blasting media (min - max)	I/h (Cu. ft. per h)	14,5 - 288 (0,5 - 10,2)
Dimensions, approx. (H x W x L)	mm Zoll	1.130 x 800 x 1.200 44,5 x 31,5 x 47,2
Weight (empty)	kg (lbs.)	200 - 240 (440 - 523)
Permissible total weight (max.)	kg (lbs.)	1.000 (2.200)

Telefon: +66 76 278038 Telefax: +66 76 279088 Email: office@tcm-asia.com

www.tcm-asia.com

TCM Asia Co., Ltd 78/23 Moo3 Kamala Kathu 83120 Phuket Thailand