



TCM torbo SoftLine

There is no nicer blasting



Developed for sensitive cleaning of monuments and facades. The advantage comes from the wet blasting equipment, which allows easy and effective gentle cleaning.

No air drier is required, no extra water hose leading to the nozzle, and no costly and heavy special nozzles. Through proprietary controls, the abrasive mixture (80% abrasives and 20% water) plus supplemental water have their flow metered separately from that of the compressed air, thereby allowing for an independent adjustment of different parameters.

With the **torbo**-System, you reduce your overheads and save the environment!

Volume of vessel	l or dm ³ (Cu. ft.)	60 (2,11)
Air connection	mm (Inch)	19 (3/4)
Compressor-connection (min - max.)	m ³ /min (Cu. ft. per min) bar (PSI)	2,0 - 4,0 (70 - 140) 4,0 - 8,0 (57 - 114)
Water connection	bar (PSI)	2,0 - 12,0 (70 -170)
Stream-connection	V (W)	12 (1,2)
Connection blasting hose	mm (Inch)	38 (1 1/2)
Consumption of blasting media (min - max)	l/h (Cu. ft. per h)	14,5 - 144 (0,5 - 5,1)
Dimensions, approx. (H x W x L)	mm Inch	1.020 x 700 x 540 40,2 x 27,6 x 21,3
Weight (empty)	kg (lbs.)	89 (196)
Permissible total weight (max.)	kg (lbs.)	300 (660)

Telefon: +66 76 278038
 Telefax: +66 76 279088
 Email: office@tcm-asia.com
www.tcm-asia.com

TCM Asia Co., Ltd
 78/23 Moo3 Kamala Kathu
 83120 Phuket
 Thailand